

AD-A070 295

NAVAL SURFACE WEAPONS CENTER DAHLGREN LAB VA

F/G 18/7

EDDY CURRENT TESTING AND ULTRASONIC REFERENCE STANDARDS FOR DEP--ETC(U)

MAR 79 C W ANDERSON




NSWC/DL-TR-79/86

NL

UNCLASSIFIED

| OF |

AD  
A070295



END

DATE

FILMED

7-79

DDC



MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

ADA070295

NSWC TR 76-88

LEVEL

12  
Na

# EDDY CURRENT TESTING AND ULTRASONIC REFERENCE STANDARDS FOR DEPLETED URANIUM BARSTOCK

by  
C. W. ANDERSON  
Weapons Systems Department

prepared for  
DEPARTMENT OF DEFENSE  
EXPLOSIVES SAFETY BOARD

DDC  
RECEIVED  
JUN 22 1978

MARCH 1978

Approved for public release; distribution unlimited

DDC FILE COPY




NAVAL SURFACE WEAPONS CENTER

Dahlgren, Virginia 22448

Silver Spring, Maryland 20910

29 06 22 029





UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER <u>14</u> NSWC/DL-TR-79/86	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) EDDY CURRENT TESTING AND ULTRASONIC REFERENCE STANDARDS FOR DEPLETED URANIUM BARSTOCK.		5. TYPE OF REPORT & PERIOD COVERED <u>9</u> Final rept.
7. AUTHOR(s) <u>10</u> C. W. Anderson		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Surface Weapons Center (Code G-53) Dahlgren Laboratory Dahlgren, Virginia 22448		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Sea Systems Command Washington DC 20362		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS OPN
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) <u>12</u> 27p.		12. REPORT DATE <u>11</u> March 1979
		13. NUMBER OF PAGES 27
		15. SECURITY CLASS. (of this report)  UNCLASSIFIED
16. DISTRIBUTION STATEMENT (of this Report)  Approved for public release; distribution unlimited.		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)  Ultrasonics Eddy Currents Depleted Uranium Nondestructive Testing		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  The design and testing of ultrasonic test standards for one-half inch (12.7mm) diameter depleted uranium barstock is discussed. This report also explores the feasibility of testing the barstock for near surface flaws using an eddy current technique. It is shown that eddy current testing is the most efficient means available for detecting surface and near surface flaws in the barstock material.		

DD FORM 1473  
1 JAN 73EDITION OF 1 NOV 65 IS OBSOLETE  
S/N 0102-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)


391 598

## FOREWORD

This report presents the results of a task performed in-house at NSWC by the Material Sciences Branch of the Survivability and Applied Sciences Division for the Ammunitions Design Agent of the Gun Systems and Munitions Division.

This report was reviewed and approved by Mr. J. D. Hall, Head, Material Sciences Branch, and Mr. D. S. Malyevac, Head, Survivability and Applied Sciences Division.

Released by:

  
LEMMUEL L. HILL  
Head, Weapons Systems  
Department

Accession For	
NTIS G.A.I.	<input checked="checked" type="checkbox"/>
DDC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or special

## CONTENTS

	<u>Page</u>
FOREWORD . . . . .	iii
LIST OF ILLUSTRATIONS . . . . .	vii
INTRODUCTION . . . . .	1
ULTRASONIC STANDARDS . . . . .	1
EDDY CURRENT TESTING . . . . .	8
INSPECTION RATES AND COSTS . . . . .	14
RECOMMENDATIONS . . . . .	17
CONCLUSIONS . . . . .	17
REFERENCES . . . . .	18
DISTRIBUTION	

# LIST OF ILLUSTRATIONS

<u>FIGURE</u>	<u>TITLE</u>	<u>PAGE</u>
1	Ultrasonic Test Standards for .5" Depleted Uranium Barstock .....	2
2	Ultrasonic A-Scan of Hole C at Nearest Point to Transducer .....	4
3	Ultrasonic A-Scan of Hole B at Nearest Point to Transducer .....	4
4	Ultrasonic A-Scan of Hole A at Center of Barstock .	5
5	Ultrasonic A-Scan of Hole B at Farthest Point from Transducer .....	5
6	Ultrasonic A-Scan of Hole C at Farthest Point from Transducer .....	6
7	Ultrasonic A-Scan of Hole D at Farthest Point from Transducer .....	6
8	Ultrasonic A-Scan of Unflawed Specimen of Extruded Rod .....	7
9	Ultrasonic A-Scan of Unflawed Specimen of Smooth Machined Rod .....	7
10	Ultrasonic A-Scan of Flawed Region of Smooth Machined Rod .....	8
11	Naturally Occurring Flaw in Barstock Material .....	9
12	Eddy Current Test System .....	11
13	Eddy Current Test Standard for .5" Depleted Uranium Barstock .....	12
14	Eddy Current Indication Caused by Barstock Wobble Within Test Coil .....	13
15	Eddy Current Indication Caused by Naturally Occurring Flaw .....	13
16	Eddy Current Indication Caused by Naturally Occurring Flaw .....	15

## INTRODUCTION

The effort reported herein was initiated to solve two problems. The first problem was the absence of any ultrasonic test standards for depleted uranium barstock purchased for the CIWS MK 149 penetrator. Such ultrasonic standards are required if the material is to be tested in accordance with Materials Specification XWS-16691<sup>1</sup> for depleted uranium barstock containing two percent molybdenum. To solve this problem, a series of ultrasonic test standards was designed, fabricated and tested.

The second problem was the inspection of the surface and near surface region of the barstock. The ultrasonic procedure developed for testing the barstock is not capable of detecting surface and near surface flaws<sup>2</sup> which is the most critical region.<sup>3</sup> To solve this problem, an eddy current inspection technique was developed, and a prototype inspection system was demonstrated.

The presence of material flaws in the barstock is of concern since they can lead to stress corrosion cracking and degraded ballistic performance of the penetrator.

## ULTRASONIC TEST STANDARDS

Materials Specification XWS-16691 states that the Material Sciences Branch at NAVSWC/Dahlgren is responsible for providing ultrasonic test standards for depleted uranium barstock as may be required by the manufacturer. The specification calls out a maximum permissible flaw size of .020 inches (.508mm) for internal defects.

A set of ultrasonic standards has been fabricated as depicted in Figure 1. These standards consist of a series of holes drilled into ends of barstock sections to represent flaws over a range of depths beneath the outside diameter. This series of holes allows for the calibration of the ultrasonic test as specified in XWS-16691 paragraph 4.4.3.1.

It should be noted that the barstock utilized for fabricating the standards mentioned above represents an "as-extruded" and thus worst case condition in terms of surface roughness (250rms). Such roughness adversely affects the performance of ultrasonic testing. Surface condition requirements are not quantitatively addressed in XWS-16691. These requirements are left to be specified in the procurement contract along with precise dimensional tolerances. Thus, standards used to accept or reject material must be fabricated from barstock which is






Figure 1. Ultrasonic Test Standards for  
.5" Depleted Uranium Barstock  
(All dimensions in inches)

representative of the condition of material used for the particular procurement. However, in demonstrating that standards fabricated from "as-extruded" barstock will work, it is automatically assured that similar standards can be fabricated for any smoother surface condition likely to be specified in the contract.

The testing of the ultrasonic standards was conducted in accordance with the procedure specified in XWS-16691. The only difference is that the output was displayed on the cathode ray tube instead of on a strip chart recorder.

Ultrasonic A-scan traces of the artificial defects in the "as-extruded" reference standards appear in Figures 2-7. The large signal on the left represents an ultrasonic reflection from the near surface of the barstock. The indication furthest to the right is the back surface echo. Echoes from the simulated flaws appear between the front and back surface indications. Each of the offset holes was detected at two depths with the exception of hole "D". This was accomplished by rotating the bar 180° so that the simulated defects were at their nearest and farthest points from the inspection transducer. Hole "D" is concealed by the front surface reflection when it is closest to the transducer. Figure 8 represents a section of barstock that is free from internal defects.

Figure 9 shows ultrasonic reflections from a smoothly machined section of barstock containing no flaws. Note the large relative increase in backwall echo amplitude in the case of a smooth surfaced (16rms) specimen. Subsurface flaws in such a specimen would be more easily detected than in the "as-extruded" specimens. The artificial defects in the extruded specimen represent the lower level of detectability and as such may not be detectable with less sensitive ultrasonic equipment. However, when the barstock surface is smooth, as with Figure 9, the signal to noise ratio is greatly improved and detection is enhanced.

Figure 10 identified a problem with the ultrasonic technique in detecting flaws near the barstock surface. The same smooth surfaced sample was used as in Figure 9. The transducer was positioned directly over a natural flaw greater than .070" which was visible from the surface (Figure 11). The flaw did not produce a discernable echo. Instead, the backwall echo disappeared indicating that the sound was being absorbed by the flaw. Rotating the barstock by 180° produced identical results. Clearly, either the backwall echo must also be monitored, which is not mentioned in XWS-16691, or an alternative technique should be used to locate near surface flaws.





Figure 2.  
Ultrasonic A-Scan of Hole C  
at Nearest Point to Transducer



PHD-0612-2-79      Figure 3.  
Ultrasonic A-Scan of Hole B  
at Nearest Point to Transducer





Figure 4.  
Ultrasonic A-Scan of Hole A  
at Center of Barstock



PHD-0613-2-79      Figure 5.  
Ultrasonic A-Scan of Hole B  
at Farthest Point from Transducer





Figure 6.  
Ultrasonic A-Scan of Hole C  
at Farthest Point from Transducer



PHD-0614-2-79      Figure 7.  
Ultrasonic A-Scan of Hole D  
at Farthest Point from Transducer








Figure 8.  
Ultrasonic A Scan of Unflawed  
Specimen of Extruded Rod



PHD-0615-2-79      Figure 9.  
Ultrasonic A Scan of Unflawed  
Specimen of Smooth Machined Rod



PHD-0616-2-79 Figure 10.  
Ultrasonic A-Scan of Naturally Flawed  
Region of Smooth Machined Rod




Figure 11.  
Naturally Occuring Flaw in  
Barstock Material  
(Scale in cm.)

PHD-1253-3-79

Note that the amplitudes of the reflections from the side drilled holes are dependent on the distance of the hole from the transducer. This is caused by the high ultrasonic attenuation of uranium, focusing of the ultrasonic beam at the center of the barstock, and the near field effects of the 15MHz transducer. This nonuniformity in inspection sensitivity can be compensated for by using a time-amplitude-correction module to equalize the reflection amplitudes. Such a module is not mentioned in XWS-16691; however, without it, the reject level will have to be set at the lowest of the reference flaw amplitudes to assure flaw detection.


#### EDDY CURRENT TESTING

Eddy current testing has a great potential for quickly and inexpensively detecting near surface flaws in depleted uranium barstock. Such near surface flaws represent the greatest threat to the structural integrity of the material.<sup>3</sup> They are more subject to corrosion and are higher stress concentrators than interior flaws.

In order to demonstrate the technique, a breadboard prototype inspection system was assembled and an eddy current reference standard was machined. The prototype inspection unit consisted of an Automation Industries EM-3300 eddy current test instrument, a pair of differential test coils, and a threshold sensing alarm circuit (Figure 12). Although both the coils and the alarm circuit were assembled in the laboratory, similar equipment can be purchased from a number of suppliers. A sketch of an eddy current standard appears in Figure 13. The .020" deep notch constitutes the standard. The .020" depth of the notch is based on the critical defect size for internal defects as specified in XWS-16691.

The eddy current instrument is a differential impedance detecting device. It compares the impedances of the two test coils driven with an alternating current at a particular test frequency, and displays the result on a storage cathode ray tube which represents an impedance plane. The position of the illuminated spot on the cathode ray tube is a function of the difference in impedance between the two test coils. When the barstock is inserted into the pair of coils, slight changes in the electrical properties of the barstock surface cause the CRT spot to be displaced. Thus, whenever a defective portion of barstock passes through the coils, a flaw indication is recorded on the CRT.

Figures 14, 15, and 16 show three different indications from the CRT of the eddy current instrument. Figure 14 shows the effect of wobbling the barstock within the slightly oversized test coils. The phase setting of the instrument was adjusted so that this indication was in



PHD-0617-2-79

Figure 12.  
Eddy Current Test System






Figure 13. Eddy Current Test Standard for  
 .5" Depleted Uranium Barstock  
 (All dimensions in inches)




Figure 14.  
Eddy Current Indication Caused by  
Barstock Wobble Within Test Coil  
(Unflawed Specimen)



PHD-0618-2-79      Figure 15.  
Eddy Current Indication Caused by  
.020" Deep Notch in Test Standard

the horizontal direction. Figure 15 shows the CRT indication caused by a .020" deep notch machined into the bar surface. Notice the indication has a vertical component in both the up and the down directions causing a "Figure 8" type of indication. This is caused by the defect passing from one coil to the next. The indication is reversed depending on which coil contains the defect at a particular instant. Figure 16 shows the indication caused by a naturally occurring defect. This is the same defect which was not detected by the ultrasonic technique.

An alarm circuit was connected to the vertical output of the test instrument. The alarm was adjusted so that when the vertical component of a flaw indication exceeded a threshold, audible and visible alarms were triggered.

The testing discussed above was performed at a frequency of 10KHz. This frequency was chosen because it is high enough to allow for good differentiation between barstock wobble indications and defect signals, and yet is low enough to provide a respectable eddy current penetration into the barstock. At 10KHz, the skin depth in uranium is .106 inches. This means that the electric field at a depth of .106 inches within the barstocks falls off to 37% or  $(1/e)$  of its strength at the barstock surface. This electric field diminishes exponentially and approaches zero near the barstock center. Thus, the further a defect is located beneath the surface, the larger it must be to be detected.

#### INSPECTION RATES & COSTS

The maximum speed at which the .5" diameter barstock can be inspected by ultrasonics will in all practicality be limited by the automatic handling equipment involved as well as the barstock straightness. The maximum ultrasonic test speed will depend on the rate at which the barstock can be rotated past the inspection transducer. For example, rotation at 300 rpm would yield an inspection speed of 15 inches per minute allowing for a 50% overlap between adjacent passes of a .1" wide ultrasonic beam. When rotating barstock at such speeds, the straightness of the material becomes critical. Thus, the ultrasonic inspection rate could well be determined by the straightness of the barstock material instead of the capabilities of the inspection system.

Eddy current testing does not require rotation of the barstock, and thus the speed would not be governed by the limitations of a rotational handling system. Eddy current testing has been demonstrated at a rate equivalent to 200 inches per minute with the test hardware described in this report. This was accomplished by manual insertion of the barstock through the test coil. Inspection speeds in excess of 1000 inches per minute could be achieved with the aid of a motorized conveyor



PHD-0619-2+79      Figure 16.  
Eddy Current Indication Caused by  
Naturally Occuring Flaw

to feed the barstock through the test coil.

To produce 120 penetrators per minute an inspection system must be capable of inspecting at least 240 inches per minute. A single ultrasonic test system will most likely fall far short of this rate. The added expense of parallel inspection stations will most likely be required for ultrasonic inspection.

Ultrasonic test instrumentation, excluding the handling system, is currently available for less than \$10,000. The cost of ultrasonic handling systems currently on the market is about \$50,000 per unit. In order to meet a production rate of 120 penetrators per minute, a single ultrasonic handling system would have to rotate the barstock at no less than 4800 rpm. This is assuming that a single transducer is used. Since this rotational speed is not practical, one would have to resort to multiple inspection units, or at least, multiple inspection stations on the same unit. The number of stations or units required will depend on the maximum rate of rotation which depends on the straightness of the barstock.

Eddy current instrumentation can also be purchased for less than \$10,000. In all likelihood, an eddy current inspection station could be set up on the same handling equipment as would be used to feed the manufacturing process. Thus, the cost of a separate handling system for eddy current testing can probably be avoided. A single automated inspection system could also keep up with a production rate of several hundred penetrators per minute.



## RECOMMENDATIONS

Based on the results of this investigation, it is recommended that:

- \* Standards for nondestructive testing be prepared based on configuration and surface conditions of the barstock or penetrators as specified in the contract.
- \* Eddy current inspection be required in conjunction with ultrasonic inspection to detect both surface and subsurface defects.
- \* Eddy current standards be prepared and made available to penetrator producers.
- \* An NDT Systems study be undertaken to define systems costs, reliability and impact on systems performance. The ultimate goal should be aimed at defining a system that provides the optimum inspection capability at the cheapest unit cost of the finished machined penetrator. A major portion of this effort should be to determine which size defects are cause for rejection based upon stress corrosion cracking and ballistic performance requirements.

## CONCLUSIONS

The ultrasonic test standards fabricated from "as-extruded" barstock demonstrate that similar ultrasonic standards can be fabricated from material with any surface condition likely to be encountered (better than 250 rms).

Complementary eddy current testing can provide a reliable and inexpensive near surface testing technique and can be applied to regions which the ultrasonic technique cannot (i.e., surface and near surface).

A single ultrasonic inspection station will most likely not be able to keep up with a barstock production rate of 240 inches per minute. Stations operating in parallel will be required.

#### REFERENCES

1. Material Specification: Barstock Depleted Uranium - 2 Percent Molybdenum, Department of the Navy, Naval Ordnance Systems Command, XWS-16691, 7 November 1975.
2. G. V. Blessing and J. M. Warren, "The Ultrasonic Inspection of Depleted Uranium Rods", 11th Symposium on Nondestructive Evaluation, Southwest Research Institute, San Antonio, Texas, 1977.
3. S. G. Fishman and C. R. Crowe, The Mechanism of Stress Corrosion Cracking in Close-In Weapons Systems Penetrators Exposed to Moist-Air Environments, NSWC/DL TR-3363, Sept 1975.

#### DISTRIBUTION

Defense Documentation Center  
Cameron Station  
Alexandria, VA 22314 (12)

Defense Printing Service  
Washington Navy Yard  
Washington, DC 20374

Library of Congress  
Washington, DC 20540  
Attn: Gift and Exchange Division (4)

National Technical Information Service  
5285 Port Royal Road  
Springfield, VA 22161

Office of the Director of Defense  
Research and Engineering  
Materials & Structures, Rm 3D1089  
Attn: Mr. J. Persh  
Washington, DC 20301

Commander  
Naval Air Systems Command  
Washington, DC 20360  
Attn: AIR-350 (Fisher)  
AIR-3501 (Marquardt)

Commander  
Naval Sea Systems Command  
Washington, DC 20362  
Attn: SEA-6422 (Nichol) (3)  
SEA-62R (Blaine)  
SEA-62R (Bailey)  
SEA-05R (Kinna)  
PMS 404-30 (Gerlach, Meinig)

Commander  
Picatinny Arsenal  
Dover, New Jersey 07801  
Attn: Technical Library

Director  
Air Force Armament Laboratory  
Eglin Air Force Base, Florida 32542  
Attn: Technical Library  
Dr. B. Kulp  
Dr. J. Cornette  
Capt. L. Lawrence  
Capt. C. Simmons

Commander  
Naval Weapons Center  
China Lake, California 93555  
Attn: Technical Library

Commander  
Naval Weapon Support Center  
NAVAMPROENGCE  
Crane, Indiana (6)

Commander  
Naval Materials Command  
Washington, DC 20362  
Attn: NAVMAT-0312 (Takle)  
NAVMAT-03J (Stone)  
NAVMAT-03422  
NAVMAT-08T23

Director  
Applied Physics Laboratory  
8621 Georgia Avenue  
Silver Spring, Maryland 20910  
Attn: Technical Library

Director  
Defense Advanced Projects Agency  
1400 Wilson Blvd.  
Arlington, Virginia 22209  
Attn: Dr. A. Bement  
C. Lehner  
Dr. M. Buckley

Director  
Air Force Materials Laboratory  
Wright Patterson Air Force Base  
Dayton, Ohio 44233  
Attn: D. A. Forney, Jr.  
Chief Nondestructive Evaluation Branch (AFMS/LLP)

Commander  
Army Materials & Mechanics Research Center  
Watertown, Massachusetts 02172  
Attn: MAD (Rizzitano, Greenspan, Levy)  
MRD (Doherty)

Commander  
US Army Armament Command  
Attn: AMSAR-RDT-L  
Dr. T. Hung  
Rock Island, Illinois 61201

Director  
Office of Naval Research  
800 N. Quincy Blvd.  
Arlington, Virginia 22217  
Attn: Code 470

Army Materials Systems Analysis Agency  
Aberdeen Proving Ground, Maryland 21005  
Attn: Dr. J. Sperraza  
Code MAXSY-D  
E. Bloore  
Code AMXBR-TB  
Dr. W. Gillich  
Code: DR-DAR-BLT

Aerospace Corporation  
P. O. Box 92957  
Los Angeles, California 09990  
Attn: Dr. G. Kendal



Union Carbide  
Oak Ridge Y-12 Plant  
Oak Ridge, Tennessee  
Attn: W. G. Northcott, Jr.

Nuclear Metals Inc.  
2229 Main Street  
Concord, Massachusetts 01742  
Attn: D. E. Ayer

General Electric Company  
Armament Systems Department  
Lakeside Avenue  
Burlington, Vermont 05401  
Attn: J. E. McGinley

Local Copy:

G  
G103  
G30  
G303  
G35  
G35 (Adams, Herron)  
G50  
G53  
G53 (Anderson) (10)  
G53 (Warren)  
G54  
R301  
R31 (Blessing)  
R32  
R32 (Crowe)  
X21 (2)

DATE  
FILMED  
-7